

MEASURING INSTRUMENTS

CatCon 6 *delta*



Measuring device for differential conductivity and pH-value determination

The analyser consists of the measuring transducer **Con 6 m** and the intelligent cation filter **CatControl 6**. It is used for continuous conductivity measurement before and after a strongly acidic cation exchanger.

Furthermore, the measuring transducer **Con 6 m** offers the option of integrating a flow measurement for monitoring the sample flow within the framework of the representative and VGB-compliant sample analysis. For a flexible use, the measuring transducer can be equipped with a broad-range mains adapter at the factory (4 wire principle). Alternatively, there is also a 2-wire-version available where separate auxiliary voltage is not required. The standardly integrated ventilation of the **CatControl 6** ensures a bubble-free sample flow even in the start-up phase.

MEASURING INSTRUMENTS

8888

The calculation of the pH-value is effected through the determination of differential conductivity in accordance with the VGB standard and provides a low-maintenance and reliable alternative in contrast to the conventional determination of the pH-value by means of a glass electrode.

Necessary preconditions for the validity of the pH-value calculation:

- use of just one alkalisating medium
- main contamination of NaCl
- pH-values > 8
- low phosphate concentration (< 0,5 mg/l)

CatCon 6 *delta*

TECHNICAL FEATURES

- Calculation of pH-value in the range of pH 7.5 to 10.5
- Simultaneous measuring of both conductivities, temperature and monitoring of sample flow
- User selectable linear and non-linear temperature compensation for various contaminations of high-purity water
- Two analogue outputs with HART protocol
- Freely usable digital contacts in the 4-wire version (washing contact, alarm, 2x limit value)



TECHNICAL DATA

MEASURING INSTRUMENTS

CatCon 6 *delta*

Device	CatCon 6 <i>delta</i>
Display	graphic display, backlit by means of colour-change status display
Operation	menu-led entry with 7 operating keys
Ambient temperature	0 ... +55 °C transport and storage temperature -30 ... +70 °C relative humidity 10 ... 95 % non-condensing
Operating parameter medium	0...+60 °C
Conductivity electrode	2x LS 06 with fixed cable
Measuring range	2x conductivity 0.001 ... 1,000 µS/cm calculation of the pH-value of 7.5 – 10.5
Accuracy	<1% of the measuring value + 0.01 µS/cm
Cation filter	1.5 l exchanger resin with colour indicator and integrated flow sensor
Sample quantity	display in l/h with digital flow sensor
Data interface	RS 485, HART
Alarm outputs	four relays as washing contact, alarm, 2x limit value (4-wire version)
Analogue outputs	one or two 0(4)...20 mA, galvanically isolated
Power supply	2-wire without auxiliary voltage 4-wire 80 V ... 230 VAC; ≤ 10 W; 45 ... 65 Hz 24 V ... 60 VDC; 10 W
Protection system	IP 67 and NEMA 4x
Weight	1,2 kg
Dimensions	1000 x 300 x 117 mm (HxWxD)

Dr. Thiedig

Subject to technical alterations.

MEASURING INSTRUMENTS



Sampling & Analysing Systems

Dr. Thiedig GmbH & Co KG
Prinzenallee 78-79
13357 Berlin | Germany

Phone +49(0)30/497769-0
Fax +49(0)30/497769-25

info@thiedig.com
www.thiedig.com

03/2014